

# e-one 10 - 48/230


(No AC In)



**e-one, stand-alone inverters a step forward!**  
**Incredible compactness and reliability, while protecting loads and batteries.**

 Telecom

 Datacom

 Mass transport

 Others

**DC In**  
48 Vdc

**AC Out**  
230 Vac

**Power**  
1 kVA  
0.8 kW

## Main Features:

e-one 10 - 48/230 is a stand-alone inverter capable of converting a **48 Vdc** power source into a **pure sine wave of 230 Vac** at 50 Hz. This inverter can deliver 1 kVA / 0.8 kW while operating from -20 to 65°C. e-one can be easily rack, wall or desk-mounted.

This inverter is available in two versions: **regular** (DC input only) and **by-pass** (AC and DC input). In by-pass version, the inverter can automatically switch from the DC source to the AC source if there are problems (with the batteries, charger or distribution). Another way to better secure your critical loads.

## Best in-class solution?


With **dimensions** of 1U x 342 mm x 221 mm, the e-one occupies just 3,300 cm<sup>3</sup> while our competitors' products are almost double the size.

e-one provides a perfect AC output (pure sine wave) that lets your **critical loads to work their best**.

We also guarantee a very low ripple voltage compliant with the telecom standard. In practical terms, this means almost no disturbances reach your DC load or **batteries**; a great benefit as disturbances considerably reduce battery life.

To minimize your **maintenance costs**, we have incorporated a variable fan speed for cooling. The fan's speed changes, or it switches off entirely, according to need. This reduces fouling and other maintenance problems.

Finally, regarding **reliability**, the e-one inverter is based on our Y-One inverter which has an incredibly low failure rate.



## Applications

e-one is the ideal solution for powering and securing any AC equipment: **telecommunication** (5G, WiFi repeaters, supervision, maintenance, cooling, security and access for base stations, etc.), **mass transport** (signalling systems for trains, GSMR along the track, etc.) and many **others** (CCTV cameras for traffic control system, police radio network, etc.).

Illustrations are non-binding and may include customized fittings.

## e-one 10 - 48/230 (No AC in)

General		No AC in (Regular)
Part Number		T551730211
Cooling / Audible noise		Forced cooling with FAN speed control / < 65 dBA at one meter
MTBF		200 000 hrs
Dielectric strength DC/AC		4250 Vdc
RoHS		Compliant
Vibration		GR63 office vibration 0 to 100 hz-0.1 g / transport vibration 5-100 Hz 0.5 g 100 to 500 hz-1.5 g / Drop test
Altitude above sea without de-rating		< 1500 m / de-rating > 1500 m – 0.8 % per 100 m
Ambient / storage temperature / relative humidity		-20 to 65° C / -40 to 70° C / 95 %, non-condensing De-rating from 40° C to 65° C
Material (casing)		Coated steel
Power		
DC Input Specifications		
Nominal voltage (DC)		48 V
Voltage range (DC)		40 - 60 V
Nominal current at 800 W / 48 VDC		19 A
Maximum input current (for 15 seconds) / voltage ripple		28 A / 2 mV psopho @ 48 V - 80% LOAD
AC Output Specifications		
Peak Efficiency DC/AC		91%
Nominal voltage		230 Vac
Frequency / frequency accuracy		50 Hz / ± 0.1%
Nominal Output power (VA) / (W)		1000 VA / 800 W
Short time overload capacity		150 % (15 seconds) within T° range
Admissible load power factor		0 lagging to 0 leading
Total harmonic distortion (resistive load)		< 3 %
Turn on delay		20 s
Nominal current. Protected against reverse current		4.35 A at 230 Vac
Crest factor at nominal power		2.5 : 1
Short circuit current duration		> 9A for 200 ms, then inverter stops and needs a manual restart
AC output voltage stability		±2% from 0% to 100% load
Signaling & Supervision		
Display		Front LED
Alarms output / supervision		Dry contact on the front
Remote ON / OFF		On the front
Standard Compliances		
Safety		IEC62040-1
Psophometric		ETS 300 386 – 2 : 2mV
EMI / EMC		EN 55032 Class A Radiated and Conducted IEC 61000-3-2 harmonic current class A EN61000-4-2 ESD criteria A - 15 kV Air and 8 kV contact EN61000-4-3 RF Field – Enclosure Port criteria A : 10 V/m EN61000-4-4 Burst - All ports criteria A : 2kV EN61000-4-5 Surge criteria B all ports EN61000-4-6 class A criteria A 10V EN61000-4-8 30 A/m

